



**DECLARATION OF PERFORMANCE Nr. 6 (DDP 6)**

**1 – Identification of the Product – Ceramic extruded porcelain floor tiles - Group A1a (E ≤ 0,5 %) – UGL (Un glazed) – Norm EN 14411:2012 (Annex M)**

**2 – Type – All sizes of extruded porcelain floor tiles - Thickness < 7,5 mm**

**3 – Intended use – Floor and Wall coverings for indoors and outdoors**

**4 – Manufacturer Identification:**

Aleluia Cerâmicas S.A.  
 Quinta do Simão – Esgueira  
 3801-101 – Aveiro – Portugal  
 Apartado 3024  
 Telephone : + 351 234 305 600 Fax + 351 234 305 699  
 Email: [geral@aleluia.pt](mailto:geral@aleluia.pt)

**5 – Not applicable**

**6 – System of Assessment / Verification - 4**

**7 – Not applicable**

**8 – Not applicable**

**9 – Declaration of Performance**

PRODUCT: Ceramic Extruded Porcelain Floor Tiles - EN 14411: 2012 - Group A1a (Annex M) – UGL Thickness < 7,5 mm			
Characteristics	Declared Values	Test Method	Norm
Reaction to Fire	Classe A1fl	-----	With no Test Reg. EU nº 305/2011
Mechanical Resistance	≥ 600 N	EN ISO 10545 - 4	<b>EN 14411:2012</b>
Flexion Resistance	In Conformity		
Mechanical Resistance	≥ 28 N/mm2	-----	
Modulus of Rupture	In Conformity		
Durability	Internal Use	In Conformity	
	External Use – Frost Resistance	In Conformity	
Thermal Shock Resistance	In Conformity	EN ISO 10545 – 9	
Slipping ( Friction Coefficient)	NPD	-----	
Anti-Slipping (for vehicles circulation)	NPD	-----	
Emission of dangerous substances (Cd and Pb)	NPD	-----	
Gluing Resistance / Adherence	NPD	-----	-----

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The present declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Elmano Castilho  
 (Quality and Ambient Director)

Aveiro, 31th January 2014

Código: FR VEN 505 Edição: 1 Revisão: 1 Data: Janeiro 2014