



ALELUIA CERÂMICAS

DECLARATION OF PERFORMANCE Nr. 7 (UKCA/DDP 7)

1 – Identification of the Product – Ceramic extruded porcelain floor tiles - Group A1a ($E \leq 0,5\%$) – UGL (Unglazed) – Norm EN 14411:2012 (Annex M)

2 – Type – All sizes of extruded porcelain floor tiles - Thickness $\geq 7,5$ mm

3 – Intended use – Floor and Wall coverings for indoors and outdoors

4 – Manufacturer Identification:

Aleluia Cerâmicas S.A.
Quinta do Simão – Esgueira
3801-101 – Aveiro – Portugal
Apartado 3024
Telephone : + 351 234 305 600 Fax + 351 234 305 699
Email: geral@aleluia.pt

5 – Not applicable

6 – System of Assessment / Verification - 4

7 – Not applicable

8 – Not applicable

9 – Declaration of Performance

PRODUCT: Ceramic Extruded Porcelain Floor Tiles - EN 14411: 2012 - Group A1a (Annex M) – UGL Thickness $\geq 7,5$ mm			
Characteristics	Declared Values	Test Method	Norm
Reaction to Fire	Classe A1fl	-----	With no Test Reg. EU nº 305/2011
Mechanical Resistance Flexion Resistance	≥ 1300 N In Conformity	EN ISO 10545 - 4	EN 14411:2012
Mechanical Resistance Modulus of Rupture	≥ 28 N/mm ² In Conformity		
Durability	Internal Use In Conformity	-----	
	External Use - Frost Resistance	EN ISO 10545 – 12	
Thermal Shock Resistance	In Conformity	EN ISO 10545 – 9	
Slipping (Friction Coefficient)	NPD	-----	
Anti-Slipping (for vehicles circulation)	NPD	-----	
Emission of dangerous substances (Cd and Pb)	NPD	-----	
Gluing Resistance / Adherence	NPD	-----	-----

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The present declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Elmano Castilho
(Quality and Ambient Director)

Aveiro, 31th October 2022

Código: FR VEN 607 Edição: 1 Revisão: 0 Data: Outubro 2022