



ALELUIA CERÂMICAS

DECLARATION OF PERFORMANCE Nr. 4 (UKCA/DDP 4)

1 – Identification of the Product – Ceramic pressed floor tiles - Group BIb (0,5 % < E ≤ 3 %) – GL (Glazed) – Norm EN 14411:2012 (Annex H)

2 – Type – All sizes of single fired ceramic floor tiles - Thickness ≥ 7,5 mm

3 – Intended use – Floor and Wall coverings for indoors and outdoors

4 – Manufacturer Identification:

Aleluia Cerâmicas S.A.
Quinta do Simão – Esgueira
3801-101 – Aveiro – Portugal
Apartado 3024
Telefone : + 351 234 305 600 Fax + 351 234 305 699
Email: geral@aleluia.pt

5 – Not applicable

6 – System of Assessment / Verification - 4

7 – Not applicable

8 – Not applicable

9 – Declaration of Performance

PRODUCT: Ceramic Pressed Floor Tiles - EN 14411: 2012 - Group BIb (Annex H) – GL Thickness ≥ 7,5 mm					
Characteristics		Declared Values	Test Method	Norm	
Reaction to Fire		Classe A1fl	-----	With no Test Reg. EU nº 305/2011	
Mechanical Resistance		≥ 1100 N	EN ISO 10545 - 4	EN 14411:2012	
Flexion Resistance		In Conformity			
Mechanical Resistance		≥ 30 N/mm2			
Modulus of Rupture		In Conformity	-----		
Durability	Internal Use	In Conformity	-----		
	External Use – Frost Resistance	In Conformity	EN ISO 10545 – 12		
Thermal Shock Resistance		In Conformity	EN ISO 10545 – 9		-----
Slipping (Friction Coefficient)		NPD	-----		
Anti-Slipping (for vehicles circulation)		NPD	-----		
Emission of dangerous substances (Cd and Pb)		NPD	-----		
Gluing Resistance / Adherence		NPD	-----		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The present declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Elmano Castilho
(Quality and Ambient Director)

Aveiro, 31th October 2022

Código: FR VEN 603 Edição: 1 Revisão: 0 Data: Outubro 2022