



ALELUIA CERÂMICAS

DECLARATION OF PERFORMANCE Nr. 6 (UKCA/DDP 6)

1 – Identification of the Product – Ceramic extruded porcelain floor tiles - Group Ala ($E \leq 0,5\%$) – UGL (Un glazed) – Norm EN 14411:2012 (Annex M)

2 – Type – All sizes of extruded porcelain floor tiles - Thickness $< 7,5$ mm

3 – Intended use – Floor and Wall coverings for indoors and outdoors

4 – Manufacturer Identification:

Aleluia Cerâmicas S.A.
Quinta do Simão – Esgueira
3801-101 – Aveiro – Portugal
Apartado 3024
Telephone : + 351 234 305 600 Fax + 351 234 305 699
Email: geral@aleluia.pt

5 – Not applicable

6 – System of Assessment / Verification - 4

7 – Not applicable

8 – Not applicable

9 – Declaration of Performance

PRODUCT: Ceramic Extruded Porcelain Floor Tiles - EN 14411: 2012 - Group Ala (Annex M) – UGL Thickness < 7,5 mm				
Characteristics		Declared Values	Test Method	Norm
Reaction to Fire		Classe A1fl	-----	With no Test Reg. EU nº 305/2011
Mechanical Resistance		≥ 600 N	EN ISO 10545 - 4	EN 14411:2012
Flexion Resistance		In Conformity		
Mechanical Resistance		≥ 28 N/mm2		
Modulus of Rupture		In Conformity		
Durability	Internal Use	In Conformity	-----	
	External Use – Frost Resistance	In Conformity	EN ISO 10545 – 12	
Thermal Shock Resistance		In Conformity	EN ISO 10545 – 9	
Slipping (Friction Coefficient)		NPD	-----	
Anti-Slipping (for vehicles circulation)		NPD	-----	
Emission of dangerous substances (Cd and Pb)		NPD	-----	
Gluina Resistance / Adherence		NPD	-----	-----

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The present declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Elmano Castilho
(Quality and Ambient Director)

Aveiro, 31th October 2022

Código: FR VEN 606 Edição: 1 Revisão: 0 Data: Outubro 2022